

STL-1280

12.1" IP65 Stainless Steel & Sunlight Readable

Monitor with Touch Screen, VGA





Features

- 12.1"LCD supports 800 x 600 pixels, high brightness 1200 nits
- Supports Full-function OSD Keys to
 Optimize the Display
- 15 pin D-sub Analog RGB 0.7Vp-p/75
 Ohm signal input

- $\odot\;$ Low power consumption
- $\odot\,$ Slim and Flat Ergonomic Design
- O Power Supply input DC 12V/24V
- O VESA Mount


Introduction

The STL-1280 is a 12.1" industrial Sunlight Readable monitor integrated with an optional 5 wire resistive touch screen. Features a 12.1" high quality SVGA TFT LCD flat panel, it presents a large display area as well as vivid and sharp images for your HMI. With Direct-VGA signal transmission, it allows Any VGA control card to be used in your system. The STL-1280 industrial monitor is designed to meet the demanding performance requirements of business and industrial applications including factory / machine / warehouse / home automation, kiosk, network communication and information terminal.

Specifications

| Model No. | STL-1280 |
|------------------------|--|
| Construction | 304 Stainless Steel, Full IP65 |
| Display | 12.1" Color Active TFT Flat Panel Display |
| Luminance | 1200 cd/m2 |
| Viewing Angle(H/V) | 160/140 |
| Resolutions | 800 x 600, 16.2M / 262K colors |
| Pixel Pitch | 0.3075 x 0.3075 mm |
| Backlight Lifetime | LED Backlight, 30,000 Hrs |
| OSD Controls | Automatic Screen, Setup (OSD), Brightness, Contrast, Horizontal/Vertical Position, Color Temperature |
| | VGA x 1; 12 VDC Jack x 1 |
| System I/O | USB x 1; RS-232 x 1 (USB & RS-232 are reserved for the Connection to enable touch usage only) |
| | IP65 (Waterproof I/O with M12 connector) |
| External Power Adapter | DC12V/5A AC-DC Adapter (100-240VAC) with or without power cord |
| Optional Touch Screen | 5 Wire Resistive with USB Interface |
| Dimensions (WxDxH) | 345mm x 275.79mm x 62.5mm |
| Operating Temperature | 0 ~ 50 °C |
| Storage Temperature | -20 ~ 60 ° C |
| Relative Humidity | 20~80%, non-condensing |
| Certification | CE |
| Vibration | 1G peak, 5~500Hz (Random) |
| Shock | 15G peak acceleration (11 msec. Duration) |
| | |

Dimensions Drawing



Ordering Information

STL-1280 12.1" IP65 Stainless Steel & Sunlight Readable Monitor

Note: All specifications and photos are subject to change without prior notice.